



SNAPTIGHT

PRODUCTS

Insulated Building Products

CARE AND MAINTENANCE GUIDE

All rights reserved.

WARNING: Drilling, sawing, sanding or machining SnapTight Products can expose you to particles of dust, a substance known to the State of California to cause cancer. Avoid inhaling the dust particles or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov. Please review prior to beginning any project.

Always follow manufacturer's installation instructions. Failure to follow manufacturers installation instructions will void manufacturer warranty.

Storage of SnapTight Products Pre-Fabricated Insulated Stucco Building Products as follows:

Prior to Installation:

- Store prefinished products off the ground, under a roof or other waterproof covering.

Touch-Up Paint Specifications:

- Touch-up paint is for installation use only.
- Touch-up paint is for professional use only.
- Touch-up paint should be used sparingly. (Example: Use to cover exposed nail heads, small nicks, or scratches less than one inch in length and less than 1/16" wide.)
- Do not apply to spots larger than 3/4" in diameter. If larger repair is required, replace the Insulated wall panel.
- Apply touch-up paint to all cut edges.
- Apply touch-up paint only when air, siding and paint temperature is above 50° F.
- Store touch-up paint at temperatures between 40° F and 100° F.
- Shake touch-up paint for 90 seconds before every use.
- Do not freeze touch-up paint. Do not use if you suspect touch-up paint has been frozen.
- Do not apply touch-up paint to SnapTight Products if wet.
- Avoid touch-up painting late in the day when dew is likely to form or when precipitation is possible.

Care and Maintenance of SnapTight Products

After Installation

- Periodic cleaning is recommended to remove dirt and dust that may build up over time. Rinse SnapTight Products Insulated Stucco Building Products with a garden hose using a low-pressure spray. Never use harsh or harmful chemicals that can damage SnapTight Products Insulated Stucco Building Products. Never use a high-pressure power washer or high-pressure nozzles.